

## CLAIMS

1. A modulation light source comprising a DBR laser having a DBR part, a phase part and a gain part; a light wavelength conversion device; and  
5 control means,

wherein the control means functions for controlling at least one of the DBR part and the phase part for modulation using a current based on a PWM signal and

10 the gain part is a part to which a substantially constant current is supplied.

2. The modulation light source according to claim 1, wherein the control means functions for controlling the DBR part for modulation using the  
15 current based on the PWM signal and the phase part is a part to which the substantially constant current is supplied.

3. The modulation light source according to claim 1, wherein the control means functions for  
20 controlling both the DBR part and the phase part for modulation using the current based on the PWM signal.

4. An image display apparatus comprising:  
the modulation light source according to claim  
1; and

25 a light deflector.

5. An electrophotographic process image display apparatus comprising:

the modulation light source according to claim

1;

a light deflector; and  
a photosensitive member.

5        6. A method of driving a modulation light  
source comprising a DBR laser having a DBR part, a  
phase part and a gain part, a light wavelength  
conversion device, and control means, comprising the  
steps of:

10        controlling at least one of the DBR part and  
the phase part for modulation using a current based  
on a PWM signal by the control means; and  
supplying a substantially constant current to  
the gain part.

15        7. The method of driving a modulation light  
source according to claim 6, wherein the  
substantially constant current is supplied to the  
phase part.

20        8. The method of driving a modulation light  
source according to claim 6, wherein both the DBR  
part and the phase part are controlled for modulation  
using the current based on the PWM signal.